



One hand grease gun-EHFP

M 10 x 1-FN-GRDR-MU

Item number: 12 250

EAN: 4103810122507

Discount group: A

Technical data

Grease gun connection, pressure-side: M 10 x 1 Filling nipple: M 10 x 1 Capacity (cm³): 500

Refilling options: 400 g grease cartridge, DIN 1284, grease gun

filling system or bulk grease

Grease pump piston actuation: manual, by means of pressure grip

Calibration Volume

Delivery rate/stroke (cm³): 1,1 Max. delivery pressure (bar): 200

Calibration Pressure

Delivery rate/stroke (cm³): 0,7 Max. delivery pressure (bar): 300

Grease gun tube colour: silver

Dimensions LxWxH (mm): 400 x 165 x 66

Weight (kg): 1,3

Specification

- Filling nipple (FN), M 10 x 1 male (12 670)
- Grease gun head, zinc die casting Z 410
- Dismantleable and movable push rod system
- Ergonomic handle
- Spout, straight, M 10 x 1, 150 mm (12 435)
- Hydraulic coupler, M 10 x 1 female (12 631)
- Packed in single carton box

Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- The construction allows a single hand operated lubrication for an easy work in restricted areas
- Can be switched with the hand grip from grease delivery with high volume to high pressure
- Due to the flexibility of the push rod, the plunger can be inserted into damaged cartridges or cartridges not exactly matching the standard dimensions
- Damaged cartridges can easily be removed
- Push rod can be locked in any position push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)
- The ease of dismantling permits simple cleaning
- Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns
- High-speed ventilation, by half a rotation of the grease gun tube
- Designed for use in rough conditions
- Similar to DIN 1283

Packaging

Dimensions LxWxH (mm): 400 x 165 x 75

Weight including package (kg): 1,43 Packing unit: 1.0